

CEP MAGNETIC EXTENSOMETER



28 Leg Magnetic Spider With Datum



6 Leg Magnetic Spider

Applications

The CEP Magnetic Extensometer is designed to measure subsurface settlement or heave in earth fill embankments, excavation, ground improvement and land reclamation projects.

Installation

Inclinometer casings or pvc access pipe with telescoping couplings are used where the soil SPT value is less than 20 blows/30cm or where total vertical or lateral movements are expected to exceed 50mm. In each installation a magnetic datum is installed at the bottom of the inclinometer or pvc access pipe. The BH is usually drilled to stable ground where the soil SPT value is at least 100 blows/30cm. The magnetic spider anchors are attached along the inclinometer casing at the specified depths. A simple triggering device is used to release the compressed spider legs to anchor at the specified depths in the soil.

Monitoring

The ground settlement or heave is measured by means of measuring the position of the spider magnets with respect to the distance from the bottom datum. The readout consists of a reed switch probe attached to an electrical tape with 1 millimeter graduations. A buzzer in the tape reel sounds when the reed switch probe passes through the magnetic fields of the spider magnets and datum. The depth of the spider anchors are read on the electrical tape.

Specifications

Model No.	Description	Length, mm	O.D. mm	Pipe O.D.	Weight, Kg
CEP2-1-70	Magnetic Spider with 28 legs	520	290	70mm inclinometer casing	0.82
CEP2-2-60S	Magnetic Spider with 6 steel legs	195	250	60mm inclinometer casing	0.22
CEP2-2-60S	Magnetic Spider with 6 steel legs (black)	230	210	60mm inclinometer casing	0.21
CEP2-2-70S	Magnetic Spider with 6 steel legs	195	265	70mm inclinometer casing	0.28
CEP2-2-70S	Magnetic Spider with 6 steel legs (black)	230	260	70mm inclinometer casing	0.23
CEP2-2-85S	Magnetic Spider with 6 steel legs	195	280	85mm inclinometer casing	0.32
CEP3-3-70	Magnetic Datum	90	70	70mm inclinometer casing	0.16
CEP3-3-85	Magnetic Datum	90	85	85mm inclinometer casing	0.18
CEP2-4	Magnetic Indicator with 50m and 100m electrical tape, marked in mm. Other lengths available upon request.				2.10

Note : Magnetic Spider can be adapted to fit 60mm O.D. PVC access pipes.

CEP SERVICES PTE LTD

30B Hillview Terrace Singapore 669248

Tel: 65-67601566 Fax: 65-67605186 Email: sales@cep.com.sg www.cep.com.sg